

Plunger Pumps



Model 277



Model 6767

SOLID SHAFT, NICKEL ALUMINUM BRONZE MANIFOLD

PUMP MODEL	MAXIMUM FLOW		MAXIMUM PRESSURE		RPM	SHAFT
	GPM	LPM	PSI	BAR		
237	2.3	8.7	1500	103	1725	16.5 mm
277	3.5	13.3	1500	103	1420	16.5 mm
247	3.6	13.7	1200	83	1725	16.5 mm
347	4.0	15.2	1800	124	1725	20 mm
317	4.0	15.2	2200	152	950	20 mm
277	4.2	16.0	1000	69	1725	16.5 mm
357	5.0	19.0	1500	103	1725	20 mm
1057	10.0	38.0	2200	152	958	30 mm
3507HS	10.0	38.0	5000	345	915	35 mm
1057	12.3	46.5	1800	124	1180	30 mm
3517HS	14.0	53.2	3000	207	800	35 mm
2537	25.0	95.0	1200	83	1025	30 mm
3527HS	25.0	95.0	2000	138	870	35 mm
3537	36.0	136.2	1200	83	800	35 mm
3537HS*	40.0	152.0	2000	138	888	35 mm
3547HS	45.0	171.0	1000	69	765	35 mm
6747	48.0	182.4	2000	138	615	45 mm
3547HS*	50.0	189.3	1500	103	850	35 mm
6767	60.0	228.0	1200	83	520	45 mm

*Intermittent duty cycle is defined as operating pump at maximum rated flow and pressure for no more than 50% of time in any given hour.