

Triethylene Glycol (TEG) Pumps, 240° F



Model 3CP1120.44101

HIGH-TEMPERATURE/TEG PUMPS, SOLID SHAFT, BRASS MANIFOLD

Belt and Bell Housing Drive

PUMP MODEL	MAXIMUM FLOW		MAXIMUM PRESSURE		RPM	SHAFT	POWER	
	gpm	lpm	psi	bar			hp	kW
3CP1130.44101	2.4	9.1	2200	152	1725	16.5 mm	3.6	2.7
5CP3105CS.44101	2.5	9.5	3500	241	1725	20 mm	6.0	4.4
3CP1140.44101	3.6	13.7	2200	152	1725	16.5 mm	5.4	4.0
5CP2120W.44101	4.0	15.2	2500	172	950	20 mm	6.8	5.1
5CP2140CS.44101	4.0	15.2	2500	172	1725	20 mm	6.8	5.1
3CP1120.44101	4.2	16.0	2200	152	1725	16.5 mm	6.3	4.7
5CP6120.44101	6.0	22.8	1600	110	1400	20 mm	6.6	4.9
1050.44101	10.0	38.0	2200	152	958	30 mm	15.1	11.2
1050.44101	12.0	45.4	1800	124	1150	30 mm	14.8	10.9
1530.44101	15.6	59.0	1500	103	1450	30 mm	16.0	11.9
1540E.44101	18.0	68.4	1200	83	1100	30 mm	14.8	10.9
2530.44101	21.0	79.8	1200	83	860	30 mm	17.3	12.8
2530.44101	25.0	95.0	1000	69	1025	30 mm	17.1	12.7
3535.44101	36.0	136.0	1200	83	800	35 mm	29.6	21.9

HIGH-TEMPERATURE/TEG PUMPS, SOLID SHAFT, 316 STAINLESS STEEL AND NICKEL ALUMINUM BRONZE MANIFOLD

Belt and Bell Housing Drive

PUMP MODEL	MAXIMUM FLOW		MAXIMUM PRESSURE		RPM	SHAFT	POWER	
	gpm	lpm	psi	bar			hp	kW
3CP1231.44101	2.3	8.7	2000	138	1725	16.5 mm	3.2	2.3
3CP1241.44101	3.6	13.7	2000	138	1725	16.5 mm	4.9	3.6
5CP6241CS.44101	4.0	15.2	2000	138	1725	20 mm	5.5	4.1
3CP1221.44101	4.2	16.0	2000	138	1725	16.5 mm	5.8	4.3
5CP6251.44101	5.0	19.0	2000	138	1725	20 mm	6.8	5.1
5CP6221.44101	6.0	22.8	2000	138	1400	20 mm	8.2	6.1
1051.44101	10.0	38.0	2200	152	958	30 mm	15.1	11.2
1051.44101	12.0	45.4	1800	124	1150	30 mm	14.8	10.9
3517.44101*	14.0	53.0	3000	207	800	35 mm	28.8	21.5
1531.44101	15.6	59.0	1500	103	1450	30 mm	16.0	11.9
1541.44101	18.0	68.4	1200	83	1100	30 mm	14.8	10.9
2531.44101	21.0	79.8	1200	83	860	30 mm	17.3	12.8
3521.44101	23.0	87.0	2000	138	800	35 mm	31.5	23.3
2531.44101	25.0	95.0	1000	69	1025	30 mm	17.1	12.7
3531.44101	36.0	136.2	1200	83	800	35 mm	29.6	21.9

*Nickel Aluminum Bronze Manifold



Model 1050.44101